



Thermory's thermally stabilised timbers offer a range of natural or pre-finished, ready to install, cladding and lining solutions. Featuring spruce and pine ranges that are responsibly sourced from sustainably grown plantation timbers. These timbers are thermally modified using heat and steam, to produce a durable, high performing product range that carries a Class 1 durability rating to perform for decades in Australian conditions.

Thermory modifies the timber for increased durability and dimensional stability in a range of natural and prefinished, ready to install exterior cladding and interior lining solutions.

Spruce Cladding Intense: Natural C26



Thermory® Spruce is an FSC certified, thermally modified softwood timber cladding. The thermal treatment strengthens the wood's molecular structure, improving the stability and resistance to moisture, rot and pests. The cladding and lining in a natural finish evokes the appearance of pine with a consistent grain, small knots and a golden tone.

Main Image: Smooth Face finish. Top Inset Image: Brushed. Bottom Inset Image: Fine Sawn detail.


Texture Natural Smooth Fine Sawn Brushed	Grade Class 1 Durability Thermally Stabilised Timber	Colour Golden tones	Species Spruce	Size (mm) 141 x 19
--	---	-------------------------------	--------------------------	------------------------------

C26 Profile:



C26: 141 x 19 / cover: 125mm

Corner Thermo - Spruce CP3



42x42

One universal profile for indoor and outdoor usage. Boards with straight-cut ends can be installed without exposing the endgrain.



CLASS 1



Durability
Improved Durability and rot resistance



Stability
Enhanced dimensional stability in changing weather conditions



Chemical-Free
Thermal modification process is entirely natural